



EFFECTS OF TURBULENCE INSTABILITIES ON LASER PROPAGATION

RCA LABORATORIES

SPONSORED GY
ADVANCED RESEARCH PROJECTS AGENCY
ARPA ORDER NO. 1279

Approved for public release; distribution unlimited.


The views and conclusions contained in this document are those of the authors and should not be interpreted as necessarily representing the official policies, either expressed or implied, of the Advanced Research Projects Agency or the U.S. Government

NATIONAL TECHNICAL INFORMATION SERVICE Springfield, Va 22151

ROME AIR DEVELOPMENT CENTER
AIR FORCE SYSTEMS COMMAND
GRIFFIST AIR FORCE BALE, NEW YORK



When W.S. Government drawings, specifications, or other data are used or any purpose other than a definitely related government procurement operation, the government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded, by implication or otherwise, as in any manner blocksing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.



Do not return this copy. Retain or destroy.

UNCLASSIFIED												
Security Classification												
	ROL DATA - R & D											
(Security ejessification of title, body of abstract and indexing	ennotes an must be entered when the everall report is classified)											
1. ORIGINATING ACTIVITY (Corporate author)	Unclassified											
RCA Laboratories Princeton, New Jersey	N/A											
A. REPORT TITLE												
EFFECTS OF TURBULENCE INSTABILITIES ON	LASER PROPAGATION											
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)	- /											
Quarterly Progress Report No. 2	9 September 1971 - 8 December 1971											
David A. de Wolf												
S. REPORT DATE	76. TOTAL NO. OF PAGES 75. NO. OF REFS											
January 1972	10 1											
F30602-71-C-0356 b. Project no. ARPA 1279	PRRL-71-CR-44											
c. Program Code 1E20	sb. OTHER REPORT HO(S) (Any other numbers that may be assigned this report) RADC TR-72-32											
10. DISTRIBUTION STATEMENT												
Approved for public release; distribut												
11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY											
Monitored by: Lt. Darryl P. Greenwood	Advanced Research Project Agency											
(315) 330-3433; RADC (OCSE) GAFB,	1400 Wilson Blvd.											
NY 13440	Arlington, VA 22209											
Three developments are reported bri spot areas under turbulent atmospheric co (b) computation of the temporal power spo	ectrum of angle-of-arrival fluctuations, or the irradiance of a plane wave leading											

UNCLASSIFIED
Security Classification LINK C LINK A LINK D 14. KEY WORDS ROLE ROLE ROLE WT WT WT Wave propagation Turbulent atmosphere, air Laser beam, focussed Optics, atmospheric Irradiance fluctuations

UNCLASSIFIED
Security Classification

EFFECTS OF TURBULENCE INSTABILITIES ON LASER PROPAGATION

DAVID A. de WOLF

CONTRACTOR: RCA LABORATORIES CONTRACT NUMBER: F30602-71-C-0356

EFFECTIVE DATE OF CONTRACT: 9 JUNE 1971 CONTRACT EXPIRATION DATE: 8 JUNE 1972

AMOUNT OF CONTRACT: \$49,990.00 PROGRAM CODE NUMBER: 1E20

INVESTIGATOR:

DR. DAVID A. de WOLF

PHONE: 609 452-2700 EXT. 3023

PROJECT ENGINEER:

LT. DARRYL P. GREENWOOD

PHONE: 315 330-3443

Approved for public release; distribution unlimited.

This research was supported by the Advanced Research Projects Agency of the Department of Defense and was monitored by Lt. Derryl P. Greenwood, RADC (OCSE), GAFB, N.Y. 13440

FOREWORD

This quarterly report was prepared by RCA Laboratories, Princeton, New Jersey under Contract No. F30602-71-C-0356. It describes work performed from 9 September to 8 December 1971 in the Communications Research Laboratory, Dr. K. H. Powers, Director. The principal investigator and project engineer is Dr. D. A. de Wolf.

The report was submitted by the author on 7 January 1972. Submission of this report does not constitute Air Force approval of the report's findings or conclusions. It is submitted only for the exchange and stimulation of ideas.

PUBLICATION REVIEW

This technical report has been reviewed and is approved.

RADC Project Engineer

ABSTRACT

Three developments are reported briefly, (a) an extension of average focal-spot areas under turbulent atmospheric conditions to non-zero elevation angles, (b) computation of the temporal power spectrum of angle-of-arrival fluctuations, and (c) development of a new formalism for the irradiance of a plane wave leading to log-normal statistics and promising a saturation effect for the irradiance (not yet computed).

BLANK PAGE

TABLE OF CONTENTS

Section																								Page
I.	PROGRE	ess	DU	JRING	THIS	Q	UAI	RTER	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1
REFEREN	CE		•				Ţ		•		•		•				•		•		•			4

I. PROGRESS DURING THIS QUARTER

The calculation of $\pi < r_L^{\ 2}>$, the average focal-spot area, has been extended to slant-path links with the transmitter at an altitude of one meter or so above the ground. We have applied the height dependence of C_n^2 given by Wyngaard, Izumi, and Collins[1]. The results are given by our previous plots of r_{oc} and r_{oL} as a function of L for diverse values of C_n^2 in horizontal propagation, supplemented by plots of $r_{oc}(\theta)/r_{oc}(0)$ for sunny-day and for dawn or dusk conditions. The same plots serve for $r_{Lc}(\theta)/r_{Lc}(0)$ because this ratio is the inverse of $r_{oc}(\theta)/r_{oc}(0)$ at any given elevation angle θ . The plots [Figures 1(a) and (b)] are independent of k (frequency) and C_n^2 (turbulence strength), hence universal.

We have computed the temporal power spectrum $W(\omega)$ of angular fluctuations, i.e., the Fourier transform with respect to τ of $<\delta\theta(t+\tau)\delta\theta(t)>$ averaged over t, for two cases:

- (a) Taylor's hypothesis which states that all movement is due to a single velocity v.
- (b) A gaussian velocity distribution of independent eddies with zero mean velocity.

In both cases, the spectrum is initially flat, then decreases with $\omega^{-2/3}$ as the angular frequency ω increases above $\omega_1 \approx v/L_0$ up to a cut-off at $\omega \approx \kappa_m L_0 \omega_1$. Further work is needed to extend case (b) to a non-zero mean velocity. The results to date are:

Case (a)

$$W(\omega) = W(\omega; 5/6) - W(\omega; 11/6)$$

$$W(\omega; \rho) = \frac{15.7}{8\pi^{1/2}} \frac{e^{2}L}{L_{o}\omega_{1}} \exp \left[-\left(\omega/\omega_{1}\kappa_{m}L_{o}\right)^{2}\right] \times \left(1 + \omega^{2}/\omega_{1}^{2}\right)^{1/2-\rho} U\left[\frac{1}{2}, \frac{3}{2} - \rho, \left(\omega^{2} + \omega_{1}^{2}\right)/\left(\omega_{1}\kappa_{m}L_{o}\right)^{2}\right]$$

where ω_1 = v/L_o and U is one of Kummer's functions in the notation of NBS Handbook of Mathematical Functions. The other symbols are defined in the previous quarterly report.

Case (b)

$$W(\omega) = W(\omega; 5/6) - W(\omega; 11/6)$$




Figure 1(a). Average-Focal-Area Parameters for Diverse Angles of Elevation.




Figure 1(b). Average-Focal-Area Parameters for Diverse Angles of Elevation.

$$W(\omega;\rho) = \frac{15.7}{8\pi^{1/2}} \frac{e^2 L}{L_0 \omega_2} \Gamma(\rho - \frac{1}{2}) U(\rho - \frac{1}{2}, \frac{1}{2}, \omega^2/\omega_2^2)$$

where $\omega_2 = 4v/L_0 \sqrt{3}$, v is the root-mean-square velocity defining the gaussian velocity probability density (for zero mean), and Γ is the gamma function.

We have worked out a new approach to the statistics of I, the plane-wave irradiance. Previously, we were critical of previous selective-summation results (including our own) because these appeared incomplete. However, much of the formalism can be retained. By making a geometrical-optics approximation in the Green's function propagator, but retaining all diffraction effects, we obtain a non-linear set of coupled equations for the field E at the point of observation $\dot{\vec{r}} = (\dot{\rho}, L)$.

$$E = E_{0} \exp \psi$$

$$\psi = \chi + i\phi$$

$$\psi = \frac{ik}{8\pi^{2}} \int_{0}^{L} dz \int d^{2}K \, \delta \tilde{\epsilon} \, (\vec{K}, z) \exp[-iK^{2}(L-z)/2k - i\vec{K} \cdot \tilde{\xi}(z)]$$

$$\vec{\xi}(z) = \vec{\rho}(L) - (L-z)k^{-1} \vec{\nabla}_{T} \phi$$

Here, $\nabla_T \phi$ is the transverse derivative of the (yet to be determined) phase function $\phi = \text{Im}(\psi)$, and $\delta \widetilde{\epsilon}$ (K,z) is a two-dimensional Fourier transform of $\delta \epsilon$ ($\vec{\rho}$,z). The log-normal behavior of E is apparent; the problem is to obtain a saturation curve for the irradiance variance. If we ignore ray bending then $\vec{\xi} = \vec{\rho}(L)$; in this case the Rytov approximation results. The next step is to include ray bending but this appears to be a difficult although promising task.

REFERENCE

1. J. Opt. Soc. Am. 61, 1646 (1971).